



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

DAP® WELDWOOD® Multipurpose Spray Adhesive

PRODUCT DESCRIPTION

DAP® Weldwood® Multipurpose Spray Adhesive is a mist spray formula that can be used for the temporary or permanent bonding of lightweight materials including carpeting, foils, plastics, papers, felt, foams, metals and cardboard.



PACKAGING	COLOR	UPC
16 oz	Clear	7079800118

KEY FEATURES & BENEFITS

- **Mist spray**
- **Provides a temporary or permanent bond**
- **Ideal for hobby & craft applications**

SUGGESTED USES

Ideal for use on:

- Trim work
- Upholstery Work

Adheres to:

- Foils
- Plastics
- Papers
- Carpeting
- Foams
- Felt
- Metals
- Cardboard



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

APPLICATION

- 1. SAFETY FIRST! PRODUCT IS EXTREMELY FLAMMABLE WHILE DISPENSING! READ AND UNDERSTAND ALL OF THE PRECAUTIONARY MEASURES FOR USE, HANDLING, STORAGE AND DISPOSAL CONTAINED IN THE PRODUCT LABEL AND SAFETY DATA SHEET (SDS).**
2. Extinguish all ignition sources during use and cure.
3. Be sure surfaces to be bonded are clean, dry, and free of excess dirt and oil.
4. Wear safety glasses and use in well-ventilated areas.
5. Shake can before use.
6. Hold can 6-8 inches from the surface to be sprayed.
7. Keep can moving while spraying to get an even film of adhesive on the surface to be bonded.
8. Make bond while the adhesive is aggressively tacky.
9. **For Temporary Bonds:** Spray one surface and allow to dry to a tack.
10. **For Permanent Bonds:** Spray both surfaces and allow to dry to a tack.
11. **Tack Range:** 1-sided application: 30 minutes. 2-sided application: 2 hours.

AFTER USE: Invert can and depress spray tip until spray is free of adhesive. If the spray tip becomes clogged, clean with a petroleum solvent.

TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Adhesive Base:	Synthetic Rubber
Volatile:	Organic solvent
Flash Point:	<20°F
Application Temperature:	60°F to 80°F
Service Temperature Range:	0°F to 150°F
Coverage:	Approximately 11 sq. ft. per can on a single surface. Coverage will vary depending on porosity of substrates.
Odor:	Solvent
Freeze Thaw Ability:	Yes
Shelf Life:	12 months

CLEAN UP & STORAGE



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

Clean excess adhesive from surfaces with mineral spirits. DO NOT use solvents to remove product from skin.

SAFETY

See product label and Safety Data Sheet (SDS) for health and safety information. You can request an SDS by visiting our website at dap.com or by calling **1-888-DAP-TIPS**.

WARRANTY

Satisfaction Guaranteed:

DAP will provide replacement product or refund sales price if product fails to perform when used as directed. Call 1-888-DAP-TIPS, with your sales receipt and product container available, to arrange for warranty fulfillment. DAP is not liable for incidental or consequential damages.

COMPANY IDENTIFICATION

Manufacturer: DAP Products Inc., 2400 Boston Street, Baltimore, Maryland 21224

Usage Information: Call **1-888-DAP-TIPS** or visit dap.com & click on "Ask the Expert"

Order Information: 800-327-3339 or orders@dap.com

Fax Number: 410-558-1068

Also, visit the DAP website at dap.com